MultiModem® GPRS
USB Wireless Modem

MTCBA-G-U-F4

MultiModem
Wireless Modem

MultiTech® Systems

User Guide

MultiTech®
Systems

MultiModem® GPRS
USB Wireless Modem
User Guide
Model MTCBA-G-U-F4
S000444C, Revision C

Copyright

This publication may not be reproduced, in whole or in part, without prior expressed written permission from Multi-Tech Systems, Inc. All rights reserved.

Copyright © 2008 by Multi-Tech Systems, Inc.

Multi-Tech Systems, Inc. makes no representation or warranties with respect to the contents hereof and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose.

Furthermore, Multi-Tech Systems, Inc. reserves the right to revise this publication and to make changes from time to time in the content hereof without obligation of Multi-Tech Systems, Inc., to notify any person or organization of such revisions or changes. Check Multi-Tech's Web site or product CD for current versions of our product documentation.

Revision History

Revision	Date	Description
A	10/04/07	Initial Release
B	03/20/08	Added Vista Operating System support. Added section on changing the GPRS Band.
C	11/17/08	Updated Vista Driver installation, added Windows Server 2008 installation, removed fax requirement, and minor editorial changes.

Trademarks and Logos

MultiModem, Multi-Tech and the Multi-Tech logo are registered trademarks of Multi-Tech Systems, Inc. Windows is a registered trademark of Microsoft in the U.S. and other countries. Other trademarks and trade names mentioned in this publication belong to their respective owners.

World Headquarters

Multi-Tech Systems, Inc.
2205 Woodale Drive
Mounds View, Minnesota 55112
(763) 785-3500 or (800) 328-9717
Fax: (763) 785-9874
Internet Address: http://www.multitech.com

Technical Support

Country	By Email	By Phone
Europe, Middle East, Africa	support@multitech.co.uk	+(44) 118 959 7774
U.S., Canada, all others	support@multitech.com	(800) 972-2439 or +(763) 717-5863

Warranty

Warranty information can be found at: http://www.multitech.com

Contents

Chapter 1 – Product Description and Specifications

Product Description

The Multi-Tech MultiModem GPRS is an external data/fax/voice wireless modem with a USB interface. It supports mobile originated short message service (SMS) and mobile-terminated SMS. Designed for global use, it offers standards-based quad-band GSM/GPRS Class 10 performance. This ready-to-deploy, standalone modem allows developers to add wireless communication to products with a minimum of development time and expense. The MultiModem GPRS is based on industry-standard open interfaces, is fully type approved, and can be desktop or panel mounted.

A Note About Documentation:
Multi-Tech Systems, Inc. reserves the right to revise this publication and to make changes from time to time in the content hereof without obligation of Multi-Tech Systems, Inc., to notify any person or organization of such revisions or changes. Check Multi-Tech's Web site for current versions of our product documentation.

Features

• GPRS Class 10 operation
• Quad-band 850/900/1800/1900 MHz
• GSM Class 1 and Class 2
• Desktop or panel mounting
• Short Message Services including text and PDU, point-to-point, cell broadcast
• 14.4K GSM circuit switched data
• SMA antenna connector and SIM socket
• Serial interface supports DTE speeds to 115.2K
• AT command compatible
• MNP2 V.42bis data compression
• Numerous LEDs provide operational status
• ME + SIM phone book management
• Fixed dialing number
• SIM Toolkit Class 2
• SIM, network and service provider locks
• Real time clock
• Alarm management
• UCS2 character set management
• Packet data up to 85K bps
• Embedded TCP/IP stack

Safety
General Safety
The modem is designed for and intended to be used in fixed and mobile applications. "Fixed" means that the device is physically secured at one location and is not able to be easily moved to another location. "Mobile" means that the device is designed to be used in other than fixed locations.

> **Caution:** Maintain a separation distance of at least 20 cm (8 inches) is normally maintained between the transmitter's antenna and the body of the user or nearby persons. The Modem is not designed for or intended to be used in portable applications within 20 cm. (8 inches) of the body of the user.

RF Interference Issues
It is important to follow any special regulations regarding the use of radio equipment due in particular to the possibility of radio frequency, RF, interference. Please follow the safety advice given below carefully.
- Switch OFF your Wireless MultiModem when in an aircraft. The use of cellular telephones in an aircraft may endanger the operation of the aircraft, disrupt the cellular network and is illegal. Failure to observe this instruction may lead to suspension or denial of cellular telephone services to the offender, or legal action or both.
- Switch OFF your Wireless MultiModem when around gasoline or diesel-fuel pumps and before filling your vehicle with fuel.
- Switch OFF your Wireless MultiModem in hospitals and any other place where medical equipment may be in use.
- Respect restrictions on the use of radio equipment in fuel depots, chemical plants or where blasting operations are in progress.
- There may be a hazard associated with the operation of your Wireless MultiModem close to inadequately protected personal medical devices such as hearing aids and pacemakers. Consult the manufacturers of the medical device to determine if it is adequately protected.
- Operation of your Wireless MultiModem close to other electronic equipment may also cause interference if the equipment is inadequately protected. Observe any warning signs and manufacturers' recommendations.

Vehicle Safety
- Do not use your MultiModem while driving.
- Respect national regulations on the use of cellular telephones in vehicles. Road safety always comes first.
- If incorrectly installed in a vehicle, the operation of Wireless MultiModem telephone could interfere with the correct functioning of vehicle electronics. To avoid such problems, be sure that qualified personnel have performed the installation. Verification of the protection of vehicle electronics should be part of the installation.
- The use of an alert device to operate a vehicle's lights or horn on public roads is not permitted.

Maintenance of Your Modem
Your Wireless MultiModem is the product of advanced engineering, design and craftsmanship and should be treated with care. The suggestions below will help you to enjoy this product for many years.
- Do not expose the Wireless MultiModem to any extreme environment where the temperature is above 50⁰C or humidity is above 90% noncondensing.
- Do not attempt to disassemble the Wireless MultiModem. There are no user serviceable parts inside.
- Do not expose the Wireless MultiModem to water, rain, or spilled beverages. It is not waterproof.
- Do not place the Wireless MultiModem alongside computer discs, credit or travel cards, or other magnetic media. The phone may affect the information contained on discs or cards.
- The use of accessories not authorized by Multi-Tech or not compliant with Multi-Tech's accessory specifications may invalidate the warranty of the Wireless MultiModem.
- In the unlikely event of a fault in the Wireless MultiModem, contact Multi-Tech Tech Support.

Your Responsibility
This Wireless MultiModem is your responsibility. Please treat it with care respecting all local regulations. It is not a toy. Therefore, keep it in a safe place at all times and out of the reach of children.

Try to remember your Unlock and PIN codes. Become familiar with and use the security features to block unauthorized use and theft.

Package Contents

Unbundled Package Modem with No Accessories	Bundled Package Modem with Accessories
1 modem 1 mounting bracket 1 Quick Start Guide 1 MultiModem CD Note: You must supply a USB cable, bracket screws, and an antenna.	1 modem 1 mounting bracket 1 USB cable 1 antenna 4 rubber feet 1 Quick Start Guide 1 MultiModem CD Note: You must supply bracket screws.

Part to be Supplied by Your Wireless Service Provider

Subscriber Identity Module (SIM) configuration chip. The SIM contains information specific to your wireless account and its features.

General Specifications

General Specifications	
Mechanical Dimensions & Weight	4.3" L x 2.4" W x 0.94" H; 4.2 oz. (11 cm x 6.1 cm x 2.4 cm; 119 g)
Connectors & Fasteners	**Antenna Connection type**: SMA jack **Interface Connector:** USB Type B **Phone Handset**: Modular handset jack **SIM receptacle**: Standard 3V SIM receptacle
Operating Temperatures	-40° to +85°C
Storage Temperatures	-40° to +85°C
Humidity	Relative humidity 20% to 90% noncondensing
Certifications and Safety	**CE Mark, R&TTE** **EMC:** FCC Part 2, 15, 22, 24, EN 55022 & EN 55024 **Safety:** cUL, UL 60950, EN 60950 **Network:** PTCRB

Functions – GSM/GPRS Modes

Mode	Description
Standard	Quad Band 850/900/1800/1900 MHz
Interface	USB interface. USB Type B.
SMS	Mobile Originated (MO) and Mobile Terminated (MT) SMS Mode Text & PDU point to point. Cell broadcast in accordance with GSM 07.05.
Data	Data circuit asynchronous, transparent, non-transparent up to 14,400 bits
GPRS	Class 10. Coding schemes: CS1 to CS4.

Electrical Specifications

Electrical Characteristics	
Switching on/off	The device is permanently powered when connected to the USB port.
Voltage	Voltage Range: 5 to 32V DC GND: 0V

Current Requirements			
Parameters	**GSM/GPRS 850/900** **Typ.**	**GSM/GPRS 1800/1900** **Typ.**	**Unit**
Input average supply current in comm. mode at P_{max}	360	300	mA
Input average supply current in idle mode	30	30	mA

RF Specifications

	GSM 850	EGSM 900	GSM 1800	GSM 1900
Frequency RX	869 to 894 MHz	925 to 960 MHz	1805 to 1800 MHz	1930 to 1990 MHz
Frequency TX	824 to 849 MHz	880 to 915 MHz	1710 to 1785 MHz	1850 to 1910 MHz
RF Power Stand	2W at 12.5% duty cycle	2W at 12.5% duty cycle	1W at 12.5% duty cycle	1W at 12.5% duty cycle

Antenna Specifications

GSM/EGSM Antenna Requirements/Specifications

Frequency Range:	824 – 960 MHz / 1710 – 1990 MHz
Impedance:	50 Ohms
VSWR:	<2.0:1
Typical Radiated Gain:	3 dBi on azimuth plane
Radiation:	Omni
Polarization:	Vertical
Wave:	Half Wave Dipole

Antennas Available from Multi-Tech Systems, Inc.

Description	Part Number
Hinged Right Angle 900/1800 MHz Cellular Modem Antenna	ANF1-1HRA
Hinged Right Angle 800/1900 MHz Cellular Modem Antenna	ANF2-1HRA
Hinged Right Angle 850/900/1800/1900 MHz Cellular Modem Antenna	ANQB-1HRA

PTCRB Requirements Note

There cannot be any alteration to the authorized antenna system. The antenna system must be the same type with similar in-band and out-of-ban radiation patterns and maintain the same specifications.

FCC Requirements Note

The antenna gain, including cable loss, must not exceed 3.0 dBi at 1900 MHz / 1.6 dBi at 850 MHz for mobile operating configurations and 7.0 dBi at 1900 MHz / 2.3 dBi at 850 MHz for fixed mounted operations, as defined in 2.1091 and 1.1307 of the rules for satisfying RF exposure compliance.

Interfaces

The Wireless MultiModem has several interfaces:
- LED function indicating operating status
- External antenna (via SMA connector)
- Serial and control link (via USB connector)
- Microphone and speaker (via handset jack)
- SIM card holder

LED Interface

LED Indicators	
TD	**Transmit Data.** Lit when modem is transmitting data.
RD	**Receive Data.** Lit when modem is receiving data.
CD	**Carrier Detect.** Lit when data connection has been established.
LS	**Line Status.** **Continuous "on" state** indicates that the wireless modem is not registered on the network. **Flashing state** indicates registration on network. **Off state**. Modem is off (not ready) or in download mode.
TR	**Terminal Ready.** Commonly called "Data Terminal Ready." This is a readiness signal from the PC.
PWR	**Power.** Indicates presence of DC power when lit.

AT Command Reference Guides

AT commands for the GPRS USB wireless modem are published in a separate GPRS AT Commands Reference Guide included on the MultiModem CD and posted on the Multi-Tech web site.

Chapter 2 – Activation and Installation

Activate Your Wireless Account

Please see the wireless account Activation Notices located on the MultiModem CD. Choose the one for your wireless network provider and follow the directions to activate your account.

Phone Numbers for the Wireless Modem
Every wireless modem will have its own unique phone number. The phone number may simply be given to you by your wireless service provider or it may be on the SIM card or both. Wireless provider implementations may vary.

Insert the SIM Card into the Holder

The wireless MultiModem requires a SIM card (Subscriber Identity Module) to operate on a GSM network. To install the card, do the following:

1. Using your fingernail or a small wedging tool (e.g., a small screwdriver), pry off the SIM cover.

2. Insert the SIM card into the holder.

3. Verify that the SIM card fits into the holder properly and then replace the cover.

Connect the Antenna and USB Cable

1. Connect a suitable antenna to the SMA connector (See antenna specifications in Chapter 1).

2. Connect the Series B end of the USB cable to the modem and the other end to the PC.

Handset Connection (Optional)

1. If you intend to use a phone handset, connect it to the MultiModem now.

Attach the Modem to a Flat Surface

This is an optional step.

To mount the Wireless MultiModem, do the following:

1. Obtain mounting screws (two are needed) that are appropriate for the surface on which you will mount the MultiModem. For example, one might use two 6-32 self-tapping screws 5/8" in length to mount the unit in a truck to the wall of the cab behind the passenger's seat.

2. Typically, the unit is mounted against a flat surface into which holes can be drilled. The mounting holes (center-to-center) must be separated by 125 mm or 4 -15/16 inches.

125 mm
or $4\,{}^{15}\!/_{16}$ inches

Multi*Modem* GPRS MultiTech®
Wireless Modem Systems

Mount to surface with bracket

Max. screw shaft
diameter = 4.3 mm (.17")

Drill the mounting holes at the desired mounting location (if applicable).

3. Slide the mounting brackets into the corresponding slots on the backside of the MultiModem chassis.

4. Attach the MultiModem with two screws to the mounting surface at the desired location on the equipment.

Install the Modem Driver

Introduction
Compatibility: This wireless MultiModem is compatible with Windows Operating Systems Vista/XP/2003/2000 and Linux.

Windows Drivers: The wireless MultiModem USB driver must be installed in your computer's program directory. The Windows USB drivers are located on the MultiModem CD in the Drivers I Windows Drivers folder. A complete set of drivers for each operating system is organized into Vista and XP with either 32-bit or 64-bit processor. For 64-bit operating systems, go to **Start I All Programs I Accessories I System Tools I Computer** and click on the **System Properties** button. Under **System** you will see **System Type: 64-bit Operating System**.

Linux Drivers: Linux Operating System drivers are also located on the CD in the **Drivers I Linux Folder**. Refer to the Readme file (also in the Linux directory) for the correct driver file and installation guide for your distribution/version of Linux.

Overview of Windows Driver Installation: Three install wizards guide you through the software Installation in this order:

- **Part A** installs the USB Driver.
- **Part B** installs the modem driver.

Installing the Modem Driver in Windows Vista

Preliminaries
1. Power up your computer.
2. If you have not already done so, connect the modem's USB cable to a USB port on the computer.
3. Windows will detect that the new modem is present.

Driver Installation of your TUSB3410 Serial Port
4. The **Found New Hardware** screen appears with Windows needs to install driver software for your TUSB3410 Serial Port.


Click on **Locate and install driver software (recommended)**. Windows will guide you through the process of installing driver software for your device.

5. The next screen prompts you to insert the disc that came with your MultiModem. If you have the disc that came with your device, insert it now.



Select **I don't have the disc. Show me other options.**

6. Choose **Browse my computer for driver software (advanced)**.

6.   At the **Browse for driver software on your computer** screen, click the **Browse** button.


7.   Browse to the **Drivers** folder on your MultiModem CD, then select the **Windows_Drivers** folder and then the **Vista32** folder. If you were installing drivers on a Vista   64-bit Operating System, you would browse to the Vista64 folder.

Click **Next**.

8.   **Windows can't verify the publisher of this driver software** screen appears.

Select **Install this driver software anyway**.

9. **Installing driver software…** screen appears.

10. When the software for this device has been successfully installed screen appears with Windows has finished installing the driver software for this device: **GSM Device**.

Click **Close.**

Installation of the Modem

11. The **Found New Hardware – MultiTech GSM Modem** screen appears. If you have the disc that came with your device, insert it now.

Click on **I don't have the disc. Show me other options.** Click **Next**.

12. Choose **Browse my computer for driver software (advanced).**

13. **Windows can't verify the publisher of this driver software** screen appears.

Select **Install this driver software anyway**.


14. **Installing driver software** progress screen appears.

15. **The software for this device has been successfully installed** screen appears. Windows has finished installing the driver software for this device: Multi-Tech Systems USB GSM_GPRS Wireless Modem


Click **Close**. The installation of drivers is now complete.

Installing the Modem Driver in Windows Server 2008, XP, 2003

This installation assumes a Windows Server 2008, XP or Windows 2003 operating system.

Installing the Serial Port

1. Connect the USB cable between the MultiModem and the PC.

2. Insert the MultiModem CD into your CD-ROM drive. The CD uses the Autorun feature, and after a brief delay, the *MultiModem Setup – Welcome* screen appears. Close the *Welcome* screen.

    In some situations the operating system will display a *Found New Hardware Wizard* screen and asks you: *Can Windows connect to Windows Update to search for software*?

    Select **No, not this time**. Then click **Next**.

2. The *Found New Hardware Wizard* screen now displays the GSM Device. This is the first of three New Hardware Wizards that will appear.

3. Click on *Install from a list or specific location (Advanced),* and then click *Next..*

4. The next screen is the *Please choose your search and installation options.* Ensure that only **Include this location in the search is selected.** Click the **Browse** button

Click the **Browse** button

5. Browse to the **Drivers** folder on your MultiModem CD, then select the **Windows_Drivers** folder and then the **XP32** folder. If you are installing drivers on an XP 64-bit Operating System, you would browse to the XP64 folder.

Click **Next.**

6. Please wait while the wizard searches for the GSM Modem. This screen only appears briefly.

7. Please select the best match for your hardware for the list below.

Click **Next.**

8. A Windows Logo Testing screen appears.

9. At the **Completing the Found New Hardware Wizard – GSM Device** screen.

Click **Finish**. Installation of the USB driver is now complete.

Installing the Modem Driver

1. If the *Welcome to the Found New Hardware Wizard* screen asking – *Can Windows connect to Windows update to search for software?* appears again.

Select **No, not this time** and then click **Next.**

2. The *Found New Hardware Wizard* screen appears for the **MultiTech GSM Modem**.

3. Click on **Install from a list or specific location (Advanced)**. Then click **Next**.
4. The *Please choose your search and installation options* screen appears.

Select **Include this location in the search** is selected. Click the **Browse** button.

**5.** If necessary, Browse to the Drivers folder on your MultiModem CD, then select the **Windows_Drivers** folder and then the **XP32** folder. If you are installing drivers on an XP 64-bit Operating System, you would browse to the XP64 folder.


Click **Next.**

6. Please wait while the wizard searches for the GSM Modem.

7. Please select the best match for your hardware from the list below.

8. The final *Windows Logo Testing* screen may appear depending on operating system settings. This screen pertains to the creation of a modem entity in the operating system that accommodates the wireless USB MultiModem.

Click **Continue Anyway**.

9. The *Completing the Found New Hardware Wizard* screen appears.

Click **Finish**.

With the modem .inf file successfully installed, the entire software installation procedure for the MultiModem is complete.

Chapter 3 – Using Your Wireless Modem

Changing the GPRS Band

All MultiModem GPRS-F4 wireless modems support quad band (850/1900/900/1800 MHz). In reality, they operate like dual, dual-band modems. In other words, they can be configured for 850/1900 or 900/1800 MHz; they do not auto-seek the local area frequency.

Build Options

The GPRS-F4 wireless modems can be ordered with a default band of 850/1900 MHz or 900/1800 MHz.

850/1900 MHz – The wireless modem defaulting to 850/1900 MHz is identified with F4 in the product ordering number. Example: MTCBA-G-F4. This build option is most commonly used in North American.

900/1800 MHz – The wireless modem defaulting to 900/1800 MHz is identified with F4-ED in the product ordering number. Example: MTCBA-G-F4-ED. This build option is most commonly used in Europe.

Changing the GPRS Band

If for any reason, such as changing the geographical area in which you use your modem, you want to change the band, you can accomplish it by using the **+WMBS** AT Command.

Steps for Changing the GPRS Band

You must use a terminal application such as HyperTerminal in order to enter the AT Command.

1. To open HyperTerminal, click **Start.** Then select **Programs > Accessories > Communications**. Then click **HyperTerminal**.
2. When the command window opens, type **AT+WMBS=<Band><Param>**. Press **Enter**.

   For **<Band>**. Enter the option you desire:
   - **4** = Dual-band mode 850/1900MHz
   - **5** = Dual-band mode 900/1800MHz

   For **<Param>**, enter the option you desire:
   - **0** = The modem will have to be reset to start on the specified band(s). This is the default.
   - **1** = The modem restarts immediately on the specified band(s).

   Example: AT+WMBS=4,0. Press **Enter**.

Phone Number for the Wireless Modem

- Every wireless modem will have its own unique phone number.
- The wireless modem's phone number may simply be told to the subscriber or be on the SIM or both. Wireless provider implementations may vary.

Examples of Useful AT Commands

A Note About HyperTerminal

In order to verify signal strength and roaming status, you must use a terminal application such as HyperTerminal. To open this program in Windows XP, go to **Start > All Programs > Accessories > Communications > HyperTerminal**. Other Windows operating systems have similar paths to HyperTerminal. See your system's online Help if you cannot find it.

A Note About AT Commands

AT commands can be used to operate, configure, and query your modem. A reference guide to the GPRS commands is included on the MultiModem CD and on the Multi-Tech Web site.

The following two commands let you query signal strength and roaming status.

Verifying Signal Strength

Using **HyperTerminal**, type **AT+CSQ**
The modem responds with the received signal strength (rssi).
The modem responds with the received signal strength (rssi) and the channel bit error rate (ber).
RSSI ranges from 0 to 31.

Signal Strength Verification – RSSI	
21 – 31	Exceptional
11 - 20	Average
0 - 10	Weak or Insufficient
99	No signal

BER ranges from 0 to 7 (Seven is the highest error rate).

Checking Network Registration and Roaming Status

In this procedure, you will verify that the Wireless MultiModem has been registered on the wireless network.
Using **HyperTerminal**, type **AT+CREG?**
The modem will respond in one of the following ways:

Network Registration Verification	
Value	**Network Registration Status**
0,0	The modem is not registered on any network
0,1	The modem is registered on the home network
0,5	The modem is registered on a network and it is roaming

Note: If the modem indicates that it is not registered, verify the signal strength to determine if the problem is the strength of the received signal.

Checking the Modem's Identity

Use the **ATI** command (Note: This command is illustrated using the capital letter i after **AT**)
- Type **ATI0** (Note: The command ends in a zero)
  The manufacturing data displays. For example: Wavecom Modem Multiband G850 1900
- Type **ATI3**
  The software version displays. For example: 651_09gg...
- Type **ATI6**
  Displays modem data features. For example: data rates, data modes, fax classes.

Establishing a Voice Call

- **Enter PIN Code (if required by your wireless provider)**
  Type **AT+CPIN=1234**
  Responses: OK (PIN Code accepted)
                      +CME ERROR : 16 (Incorrect PIN Code)
                      +CME ERROR : 3 (PIN already entered [with +CMEE : 1 mode])
- **Initiate a voice call**
  Type **ATD1234;**   (Note: Don't forget the semicolon ";" at the end. This stands for *voice* calls)
  Responses: OK (Communication established)
                      CME ERROR : 11 (PIN Code not entered [with +CMEE : 1 mode])
                      CME ERROR : 3   (Operation not allowed)
- **Initiate an emergency call**
  Type **ATD112;** (Note: Don't forget the semicolon ";" at the end. This stands for *voice* calls)
  Responses: OK
- **Hang up**
  Type **ATH**
  Responses: OK

Establishing a Circuit-Switched Data (CSD) Connection

A Circuit-Switched Data Connection (CDC) makes the wireless modem work similar to a regular analog modem. You must have CSD service in order to make a CSD call. Note that your wireless provider charges airtime usage for these connections.

Note: Your cellular provider charges airtime usage for these connections.

Establish a Connection: Using HyperTerminal or a terminal application, you can establish a CSD connection by entering the following command: **ATD<phone number>**

Notes:
- The phone number you are calling is entered between the displayed brackets. Do not type additional brackets. For example, type only **ATD 8585551212**. **8285551212** is typed between the brackets.
- This command tells the modem to inform the wireless network that you are initiating a CSD modem call. If you are dialing to another modem, the remote modem should answer and a connection between the two modems will be established. If you include a semi-colon (;) at the end of the dialing string, the modem will instead initiate a Voice call to the phone number dialed.

Disconnect: Type: **+++**
Wait about two seconds to see an OK response.
Then type: **ATH**
Note: +++ is the escape sequence and **ATH** is the Hang-up command.

Answering a Circuit-Switched Data (CSD) Connection

A Circuit-Switched Data Connection makes the wireless modem work similar to a regular analog modem. You must have CSD service in order to answer a CSD call.

There are three phone numbers for GSM: the voice number, the data number, and the fax number. All are provided by the carrier. To answer a call:

Establish A Connection: Call into the modem by dialing the data number provided by your carrier.

Answer a Call: When you see the RING responses on the terminal screen, enter **ATA <cr>** to answer the call.

Set Auto-Answer: Enter **ATS0=_x_**
This sets the modem to auto-answer. The call will be answered after the number of rings entered. _x_ stand for the number rings.
Then call into the number provided to you by the carrier.

Disconnect: Type: **+++**
Wait about one second to see an OK response.
Then type: **ATH**

Using Short Message Services (SMS)

Send a Short Message to a Specified Number.
Type **AT+CMGS="8585551212" <press Enter>**
Then type your message: **Please call me soon. <press ctrl Z>**
The modem may respond with **+CMGS:<mr> OK**

Write a Message to Memory.
You can store a message to send it at a later date.
Type **AT+CMGW="8585551212" <press Enter>**
Type the message. **<press ctrl Z>**
The modem may respond with **+CMGW: 4 OK** (The message is stored in the index as message 4.)

Send a Message from Storage.
Type **AT+CMSS=_x_,"8585551212" <press Enter>**
The modem may respond with **+CMSS: 1 OK** (The transmission is successful. One SMS message is sent.)
Note: The _x_ represents an index location.

View a List of Stored Messages.
Type **AT+CMGL=x <press Enter>**
For **x**, substitute one of the following:

"REC UNREAD" Shows received unread messages.
"REC READ" Shows received read messages.
"STO UNSENT" Shows stored unsent messages.
"STO SENT" Shows stored sent messages.
"ALL" Shows messages.

The modem will respond **AT+CMGL: 1,"REC UNREAD","8585551212",1...**
The modem will continue until all UNREAD messages, numbers, and index number are listed.

Read a Stored Message.
Type **AT+CMGR=x <press Enter>**
The modem may respond with **+CMGR: "REC READ", "8585551212", ...**
Note: The **x** represents an index location.

Delete a Stored Message.
Type **AT+CMGD=x,n <press Enter>**
If you want to delete one message at a time, do not enter a value for **n**.
For **n**, substitute one of the following:

0 Delete message at location <include the index number>
1 Delete all READ messages.
2 Delete all READ and SENT messages.
3 Delete all READ, SENT, and UNSENT messages.
4 Delete ALL messages.

The modem will respond **OK.**
Note: The **x** represents an index location. The **n** stands for the type of messages to delete.

SMS Examples

Send Example

Send an SMS message to another SMS compatible device

at+cmgf=1 (set to text mode)
OK
at+cpms="SM","SM" (set memory storage when writing and sending SMS messages)
+CPMS: 0,50,0,50

OK

at+cmgs="7632273726" (send message to the number specified in quotes)
> TEST message ONE. (Type message after the > symbol and hit <CTRL + Z> to send the message)
+CMGS: 52

OK

Receive Examples

Receive Example 1: Receive SMS messages in text mode by saving to SIM memory – Notification via +CMTI unsolicited response code:

at+cmgf=1 (set to text mode)
OK
at+csms=0 (set to Phase 1)
+CSMS: 1,1,1

OK
at+cnmi=2,1,0,0,0 (set to display +CMTI indication when SMS is received)
OK
at+cpms="SM","SM" (set the read and write storage of SMS to SIM)
+CPMS: 0,50,0,50

OK

+CMTI: "SM",1 (indication that message was received and stored to SIM location 1)
at+cmgr=1 (read message stored in location 1)
+CMGR: "REC UNREAD","+17632273726",,"06/03/17,13:55:22+00"
TEST1

OK
at+cmgd=1 (delete message that is stored in location 1)
OK

Receive Example 2: Receive SMS message in text mode by directly routing the received message to the TE through the serial port using Phase 2:

at+cmgf=1 (set to text mode)
OK
at+csms=0 (set to Phase 2)
+CSMS: 1,1,1

OK
at+cnmi=2,2,0,0,0 (set to receive SMS and route directly to TE)
OK

+CMT: "+17632273726",,"06/03/17,13:59:18+00" (message received and directly routed to TE)
TEST2

Receive Example 3: Receive SMS message in text mode by directly routing the received message to the TE through the serial port using Phase 2+:

at+cmgf=1 (set to text mode)
OK
at+csms=1 (set to Phase 2+)
+CSMS: 1,1,1

OK
at+cnmi=2,2,0,0,0 (set to receive SMS and route directly to TE)
OK

+CMT: "+17632273726",,"06/03/17,14:01:17+00" (message received and directly routed to TE)
TEST3
at+cnma (acknowledge that message has been received)
OK

Internet Access

Internet access can be setup in Windows Dial-Up Networking (DUN) of the computer that the wireless modem is serving. Setup procedures will vary according to the type of wireless service provider used. To access *Dial-Up Networking* on your PC, go to **Start > Settings > Network Connections**.

- For GSM-without-GPRS, a circuit-switched data connection is used. The user can set up DUN to make a conventional V.32 modem connection to any terminating modem at the other end. The phone number specified in DUN can be one supplied by the wireless service provider or another phone number related to a different dialup modem service (e.g., a dialup modem service phone number from any commercial or private dialup network).
- For GSM-with-GPRS, a single DUN number is generally used by all of a wireless provider's subscribers throughout its area of coverage; regional, nationwide, continental, etc. Rather than being a literal phone directory number, as in conventional DUN, this is a code that gives the modem Internet access.

Connecting to the GPRS Network for Internet Access

After you have inserted the SIM card and the modem is ready for use, you can establish an Internet connection through a Windows dial-up session.

Note that your wireless provider will charge you for data usage.

Requirements
- One Multi-Tech wireless GPRS modem
- The GPRS modem should have an active SIM card and must have GPRS services
- The modem must be getting a proper signal and be showing a network registration through the wireless provider's network
- A PC running Windows Vista, XP, or 2003 with the Multi-Tech drivers installed for your particular model

Notes:
- The following instructions are for Windows XP SP2 and Windows 2003. Every PC may have slight differences which may cause the instructions to be different. Use these instructions as a guide to help you understand what is required to set up an Internet connection through your wireless service provider for all operating systems.
- Cellular providers provide Internet services as part of your service plan. Multi-Tech recommends that if you plan on using large amounts of data, to sign up for an unlimited data service plan with your provider. Multi-Tech Systems, Inc. will not be responsible for any charges on your cellular bill. If you have any questions about billing, service plans, service charges, etc., please contact your provider for more information.

Set the Access Point Name (APN) into the Modem's Properties on Your PC

In order for your GPRS wireless modem to connect to your provider's network, you must tell the modem the Access Point Name (APN) to which it will connect. The APN is a server name that your account is setup on with your provider. Your APN will be given to you by your provider. Here are some well-known APNs:

- AT&T: PROXY, or INTERNET, or PUBLIC
- T-Mobile: INTERNET2.VOICESTREAM.COM, or INTERNET3.VOICESTREAM.COM, or WAP.VOICESTREAM.COM
- Rogers AT&T of Canada: INTERNET.COM

Steps for Setting the APN
1. Start by clicking on **Start** and then clicking on **Control Panel**.
2. In the Control Panel, double-click on **Phone and Modem Options**.
3. The *Phone and Modem Options* window appears. Click on the tab labeled **Modems**. Highlight the Multi-Tech wireless modem listed in the table and then click on **Properties**.
4. A *Properties* window for your modem will display. Click on the **Advanced** tab and you should see an *Extra Settings* box. In the **Extra initialization commands** text box, type:

    AT+CGDCONT=1,"IP","<APN>"
    For <APN>, type in the correct APN for your account. For example:
    AT+CGDCONT=1,"IP","ISP. AT&T"

    Click **OK** to close the modem *Properties* window. Then click **OK** to close the *Phone and Modem Options* window.

Create Your Dial-Up Connection in Windows Vista, XP, 2003, and 2000

1. Click on **Start** and then click on **Control Panel**.
2. In the *Control Panel*, double-click on **Network Connections**.
3. On the *Network Connections* screen on the left-hand side under **Network Tasks**, click on **Create a new connection**.
4. The *New Connection Wizard* should appear. It will walk you through setting up your Internet connection. Click on **Next >** to begin.
5. On the *Network Connection Type* screen, select **Connect to the Internet**, and then click **Next >**.
6. On the *Getting Ready* screen, select **Set up my connection manually**, and then click **Next >**.
7. On the *Internet Connection* screen, select **Connect using a dial-up modem**, and then click **Next >**. **Note:** After clicking on Next, you may or may not be asked to select which modem to use. If you have more than one modem installed in your PC, you will be required to select the proper modem to use. If asked, please select the Multi-Tech wireless modem that has been installed.
8. On the *Connection Name* screen in the **ISP Name** box, type in a name for your new connection. You can give it any name that you would like. After you have typed in a name, click **Next >**.
9. On the *Phone Number to Dial* screen, type in the number that specifies to the modem to connect to your provider's Internet service.

   For GPRS modems, type in the number ***99***1#.**
   Then click **Next >**.

10. On the *Connection Availability* screen, specify if this connection is for anyone's use or for your use only by checking the appropriate button. Choose your preference, and then click **Next>**.
11. On the *Internet Account Information* screen, type the user name and the password for your account. In many cases, a user name and a password are not required, but some wireless providers require it. Check with your provider to see if they are needed.
    Check the following two options if you would like them activated:
        Check the box if you want this account name and password to be used by everyone.
        Check the box if you want this as your default Internet connection. Then click **Next >**.
12. On the *Completing the New Connection Wizard* screen, you last task is to place a check in the box if you would like to add a shortcut to your desktop. Then click **Finish**.
13. A *Connection* screen displays on your desktop. Click the **Properties** button on the bottom of this screen.
14. The *Properties* window will open for you to make your connection. **Important:** Make sure that *Use dialing rules* is not selected, and then click **OK**.
15. Once back at your *Connection* screen, click the **Dial** button at the bottom of the screen to start the connection.
16. The connection will now tell the modem to connect to your provider's Internet service. Once connected, you should see the connection status icon in your system tray at the bottom right-hand corner of your screen.

    You should now be able to open Internet Explorer or any other browser of your preference to surf the Internet.

Disconnecting the Connection:

1. To disconnect the connection, right click on the connection icon in your system tray at the bottom right-hand corner of your screen.
2. Scroll up and click on **Disconnect**.
   Your should now be disconnect from the Internet.

Chapter 4 – Troubleshooting and Frequently Asked Questions

Troubleshooting Examples

Before calling the Multi-Tech Technical Support, check to the following connections:

- The right antenna is connected to the modem
- The serial cable connection is correct
- The power is connected correctly and the power lights on the modem are on
- Verify your signal strength
- Verify your network registration
- Use the following situation examples to troubleshoot the modem not answering and the modem returning a *No Carrier* message.

Situation A: The modem does not answer

If the Wireless MultiModem does not answer through the serial link upon an attempted transmission of data or voice signals, see the table below for possible causes and solutions.

Solutions for 'no connection through serial link' situation		
If the modem returns …	**Then ask …**	**Action**
(nothing)	Is the communication program properly configured?	In communications program, verify that modem parameters have been set to the values shown here: Data bits = 8 Parity = none Stop Bits = 1 Baud = 115200 bps
	Is another program interfering with the communication program?	Close any such application program.
	Is the modem set to autoanswer?	Type **ATS0=1** (to set to auto answer on the first ring) Type **ATA** (to set to manual answer)
	Is the communication program receiving RING responses?	Type **ATS0=1** (to set to auto answer on the first ring) Type **ATA** (to set to manual answer)

Situation B: The modem always returns «No carrier» when trying to originate a call

Solutions for "no carrier" message		
If the modem returns …	**Then ask …**	**Action**
no carrier *(esp. for data communication)*	Is the selected bearer type supported by the called party? Is the selected bearer type supported by the network?	Type AT+CEER to view the extended error code (see "Error Results Codes" in the AT Command guide). Be sure that the selected bearer type is supported by the called party. Be sure that the selected bearer type is supported by the network. If no success, try bearer selection type: AT+CBST=0,0,3 Be sure SIM card is available for data/fax calls.
no carrier *(esp. for voice communication)*		Be sure that the semicolon character (";") is typed immediately after the phone number in the AT command; e.g., ATD######;

Frequently Asked Questions

Which providers can I use?
- Two major providers are T-Mobile and AT&T.

Does this modem support High-Speed Circuit-Switched Data (HSCSD)?
- No, our GSM/GPRS modems do not support HSCSD.

The modem is answering, but seems to not be doing anything?
- The modem is answering in voice mode.
- If you are trying to make a data call, make sure the account has CSD service. You will also need the data number (separate number from the main phone number that is provided by the provider).

I am trying to make a data connection by dialing from my wireless modem to an analog modem. Why does the analog modem answer and send tones, but never connect?
- To make a data call you must use the ATD<number> command.
- Make sure the account has CSD service.

How do I get the voice portion to work so I can talk to others using the wireless modem?
- You will need a cable that has the speaker pins connected to a speaker and microphone.
- We have a "Y" cable that splits out to a RJ9 connector that can be used to plug into the receiver of a handset.
- 'ATD<number>;' will originate a voice call.

How do I make an Internet connection to my dial-up ISP?
- Make sure you have CSD service.
- Create a dial-up connection to the ISP's access number, then use your account username and password and choose the wireless modem as the device.

How does faxing work?
- GPRS modems support Class 1 and Class 2 Group 3 faxing.
- You will need fax services setup on your account. You should receive a separate phone number for fax just like voice and data, and you must call the fax number for the modem to receive a fax.
- You will also need fax software (we do not have working software). WinFax Version 10 has been tested with success.

I can't make outgoing calls. I just receive a NO CARRIER response.
- Make sure the antenna is connected and SIM is inserted correctly.
- Check signal and registration: 'AT+CSQ' (10-31 is good), 'AT+CREG?' (0,1 is registered & 0,5 is roaming).
- Check NO CARRIER reason with 'AT+CEER'. Look up error code in Reference Guide.

The modem will not answer.
- To have modem autoanswer, set modem with 'ATS0=1' and 'AT&W' to store the setting.
- Send 'ATA' to the modem once the RING is indicated on the terminal screen.
- You may need to set modem to ignore DTR, 'AT&D0', if you aren't providing DTR.

I am trying to make a GPRS connection using a Windows dial-up session. It connects and then immediately disconnects.
- Make sure the APN is configured in the modem correctly (The APN is provided by the provider).
- Check the APN with 'AT+CGDCONT?' To make sure it is correct.
- If no APN is inserted, then insert the correct APN using the command 'AT+CGDCONT=1,"IP","<APN>"' with HyperTerminal or add it into the "Extra Initialization Commands:" in the modem's properties.
- Make sure the APN is correct for your account.

When I try to establish a GPRS connection using Windows dial-up I get an error: "Hardware Failure".
- Check the modem to make sure it is installed and can be queried in the modem's properties.
- Make sure the com port is not being held by another application. Look for the TR light indication. If it is on, most likely another application is holding onto the port.
- Make sure the dial-up connections maximum speed matches the modem's properties maximum port speed.
- Try rebooting the PC.

What is the maximum amount of characters I can use to send an SMS message?
- Supports up to 160 characters maximum.
- In PDU mode using 7-bit, the modem still supports 160 characters, but in 8-bit the modem will support only 70 characters.

After changing the +CNMI, +CSCA, or +CSMP command values, the modem doesn't store them.
- When changing these command values, you must use the +CSAS command to store the changes.

How do I send an SMS message to an email account?
- When sending an SMS message to an email account, you must use a designated routing number that will tell the SMS server to route your message to an email account. Here are the numbers that we are aware of at this time:

> AT&T = "0000"
> T-Mobile = "500"

Here is an example of how to send an SMS message to an email account:
> AT+CMGS="0000"
> > email@multitech.com My message goes here. <ctrl +Z>

Appendix A - Waste Electrical and Electronic Equipment (WEEE) Statement

July, 2005

The WEEE directive places an obligation on EU-based manufacturers, distributors, retailers and importers to take-back electronics products at the end of their useful life. A sister Directive, ROHS (Restriction of Hazardous Substances) complements the WEEE Directive by banning the presence of specific hazardous substances in the products at the design phase. The WEEE Directive covers all Multi-Tech products imported into the EU as of August 13, 2005. EU-based manufacturers, distributors, retailers and importers are obliged to finance the costs of recovery from municipal collection points, reuse, and recycling of specified percentages per the WEEE requirements.

Instructions for Disposal of WEEE by Users in the European Union
The symbol shown below is on the product or on its packaging, which indicates that this product must not be disposed of with other waste. Instead, it is the user's responsibility to dispose of their waste equipment by handing it over to a designated collection point for the recycling of waste electrical and electronic equipment. The separate collection and recycling of your waste equipment at the time of disposal will help to conserve natural resources and ensure that it is recycled in a manner that protects human health and the environment. For more information about where you can drop off your waste equipment for recycling, please contact your local city office, your household waste disposal service or where you purchased the product.